TENSION SHADES Skylight 2 FlexShade®

LARGE APPLICATIONS OVERHEAD GLAZING PROTECTION



Skylight 2 FlexShade, Insurance Institute for Highway Safety, Ruckersville, VA Dealer: Direct Path, Alexandria, VA., Photography: Ron Dressel Photography, Ruckersville, VA

Skylight 2 FlexShade® offers motorized solar control for very large skylight applications. This window shade protects against solar heat gain and controls glare, protecting staff and furnishings from overhead sunlight, while creating a comfortable work environment.

FEATURES

- Install at any angle, as long as rollers are level and parallel to the floor.
- Light gap 2 $\frac{7}{8}$ " (73 mm) on three sides-variable gap due to fabric bundle diameter on roller end.
- Draw-cable/guide-cable brackets provided with pulley assemblies.
- Nylon coated cables are low-stretch, high-fatigue.
- Built-in pulley assemblies for routing of draw cable.
- Guide cables 3/16" (5 mm).
- Draw cables 1/16" (2 mm).

- Horizontal spring steel stays to withstand reasonable air pressure differentials and gravity.
- Adapter bracket white powder coat finish.
- Endcaps 5 13 /₁₆" x 5 13 /₁₆" (130 cm x 130 cm).
- Spline attached fabric.
- Product designed for interior use.

OPTIONS

 Hardware finish choices: clear anodized (standard), black, white, ivory, or charcoal bronze. Custom powder coat colors available.

SIZES

 Available in sizes up to 13' wide x 20' high (396 cm x 610 cm), depending on fabric selection.

FABRIC OPTIONS

draperinc.com/windowshades/fabricoptions. aspx

WARRANTY

draperinc.com/warranty.aspx

SUPPORTING DOCUMENTS

All instructions, technical drawings and other supporting documents are located at: *draperinc.com/documents.aspx*

For more information on this product visit: *draperinc.com/windowshades/tensionshades. aspx*

