

Shade Fabric Reference Sheet

by **DRAPER**

Please use this form as a reference. Fabric name, color and number must be entered on the submittal form for the shade product being specified.

Specifications—Fabrics

Phifer

SheerWeave Basic by Phifer. For interior use only, 38 percent fiberglass, 62 percent vinyl on fiberglass with Microban Protection. Flame retardant per NFPA 701, BS 5867-2 and CAN/ULC-S109.3). Bacteria and Fungi Resistant per ASTM D3273, ASTM D6329, ASTM E2180 and ASTM G21. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Lead free certified per RoHS. Chemical compliant per REACH (EC 1907/2006). Openness Factor: 3 or 5 percent in accordance with ASHRAE 74. Colors available: White/Bone, White, White/Platinum, Charcoal/Grey and Charcoal.

3% Open: Thickness: .025 inches. Weight: 16.4 oz./sq. yd.

5% Open: Thickness: .022 inches. Weight: 14.1 oz./sq. yd.

SheerWeave Infinity by Phifer. For interior use only. PVC-free, lead free, and 100 percent recyclable. Made from core yarn, synthetic or natural, that comes from post-industrial waste by product. 100 percent TPO composition. Flame retardant per NFPA 701. Bacteria and Fungi Resistant per ASTM E 2180. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Lead free certified per RoHS. Openness Factor: 3 or 5 percent in accordance with ASHRAE 74. Colors available: Almond, Bark, Barley, Cotton, Midnight, Nickel, Slate, Stone and Wheat.

3% Open: Thickness: 0.043 inches. Weight: 18 oz./sq. yd.

5% Open: Thickness: 0.043 in. Weight: 15.3 oz./sq. yd.

SheerWeave Series PW3500/4100/4400 by Phifer. For interior use only. Vinyl-coated polyester, flame retardant, woven into a 2 x 2 basketweave with Microban Protection. Flame retardant per NFPA 701, BS 5867-2 and CAN/ULC-S109.2) California U.S. Title 19 compliant. Bacteria and Fungi Resistant per ASTM E2180. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Lead free certified per RoHS. Chemical compliant per REACH (EC 1907/2006). Colors available: Snowy White (Chalk), Bone (Pebblestone), Greystone, Soft Grey (Pewter), Granite, Ash, Linen (Alabaster), Ebony (Black) and Tobacco.

PW3500: Openness Factor: 5 percent in accordance with ASHRAE 74. Thickness: 0.036 inches. Weight: 19.2 oz./sq. yd.

PW4100: Openness Factor: 10 percent in accordance with ASHRAE 74. Thickness: 0.035 inches. Weight: 17.5 oz./sq. yd.

PW4400: Openness Factor: 3 percent in accordance with ASHRAE 74. Thickness: 0.037 inches. Weight: 20.70 oz./sq. yd.

SheerWeave Series PW4500/4600 by Phifer. For interior use only. Vinyl-coated polyester, flame retardant with Microban Protection. Flame retardant per NFPA 701, BS 5867-2 and CAN/ULC-S109. California U.S. Title 19 compliant. Bacteria and Fungi Resistant per ASTM E 2180. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Lead free certified per RoHS. Chemical compliant per REACH (EC 1907/2006). Colors available: Chalk, Granite, Ecru, Golden Sand, Ebony, Sandstone, Sable, Linen, Cappuccino, Pewter and Dark Bronze.

PW4500: Openness Factor: 5 percent in accordance with ASHRAE 74. Thickness: 0.024 inches. Weight: 14.40 oz./sq. yd.

PW4600: Openness Factor: 3 percent in accordance with ASHRAE 74. Thickness: 0.030 inches. Weight: 17.40 oz./sq. yd.

SheerWeave Series PW4550/4650 by Phifer. For interior use only. Vinyl coated polyester yarn woven into basketweave pattern with Microban Protection. Flame retardant per NFPA 701, BS 5867-2 and CAN/ULC-S109. California U.S. Title 19 compliant. Bacteria and Fungi Resistant per ASTM E2180. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Lead free certified per RoHS. Chemical compliant per REACH (EC 1907/2006). Colors available: Granite, Linen, Coal and Chestnut.

PW4550: Openness Factor: 5 percent in accordance with ASHRAE 74. Thickness: 0.025 inches. Weight: 12.5 oz./sq. yd.

PW4650: Openness Factor: 3 percent in accordance with ASHRAE 74. Thickness: 0.026 inches. Weight: 13.30 oz./sq. yd.

SheerWeave PW4800 by Phifer. For interior use only. 24 percent vinyl-coated polyester and 76 percent vinyl with Microban Protection. Flame retardant per NFPA 701, BS 5867-2 and CAN/ULC-S109. California U.S. Title 19 compliant. Bacteria and Fungi Resistant per ASTM D3273, ASTM D6329,

ASTM E2180 and ASTM G21. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Lead free certified per RoHS. Openness Factor: 1 percent in accordance with ASHRAE 74. Thickness: 0.036 inches. Weight: 18.5 oz./sq. yd. Colors available: Alabaster, Grey, Chalk, Pearl, Mocha, Sand, Taupe, Clay, Fleece, Mink, Flint and Ebony.

SheerWeave SW1000 by Phifer. For exterior FlexShade Panel use only. Fabric Content and Structure: 35% Fiberglass, 65% Vinyl on Fiberglass in a ribbed weave. Flame retardant per California U.S. Title 19 (small scale), NFPA 701 TM#1 (small scale), BS 5867-2 and NFPA 701 TM#2 Large Scale. Bacteria and Fungal Resistant per ASTM D3273, ASTM D6329, ASTM E2180 and ASTM G21. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Lead free certified per RoHS. Openness Factor: 25 percent in accordance with ASHRAE 74. Thickness: .020 in. Weight: 8.8 oz./sq. yd. Colors available: White and Antique White.

SheerWeave Series SW2000/2100 by Phifer. For interior use only. 63 percent PVC-coated fiberglass and 37 percent fiberglass yarns, 500 denier, woven into a 2 x 2 non-directional basketweave with Microban Protection. Flame retardant per NFPA 701, BS 5867-2 and CAN/ULC-S109. California U.S. Title 19 compliant. Bacteria and Fungi Resistant per ASTM D3273, ASTM D6329, ASTM E2180 and ASTM G21. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Lead free certified per RoHS. Colors available: White, White/Bone, Bone, Bone/Platinum, White/Platinum, Platinum, Bronze, Charcoal, Charcoal/Grey and Charcoal/Chestnut.

SW2000: Openness Factor: 5 percent in accordance with ASHRAE 74. Thickness: 0.019 inches. Weight: 14.26 oz./sq. yd.

SW2100: Openness Factor: 10 percent in accordance with ASHRAE 74. Thickness: 0.020 inches. Weight: 14.40 oz./sq. yd.

SheerWeave Series SW2400/2500/2600 by Phifer. For interior use only. 65 percent PVC-coated fiberglass and 35 percent fiberglass yarns, woven into a 2 x 2 non-directional basketweave with Microban Protection. Flame retardant per NFPA 701 and BS 5867-2. California U.S. Title 19 compliant. Bacteria and Fungi Resistant per ASTM D3273, ASTM D6329, ASTM E2180 and ASTM G21. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Lead free certified per RoHS. Chemical compliant per REACH (EC 1907/2006). Colors available: Oyster, Oyster/Beige, Oyster/Pearl Grey, Beige, Beige/Pearl Grey, Pearl Grey, Charcoal, Charcoal/Alpaca, Charcoal/Grey and Charcoal/Chestnut.

SW2400: Openness Factor: 3 percent in accordance with ASHRAE 74. Thickness: 0.019 inches. Weight: 13.9 oz./sq. yd.

SW2500: Openness Factor: 1 percent in accordance with ASHRAE 74. Thickness: 0.024 inches. Weight: 16.10 oz./sq. yd.

SW2600: Openness Factor: 10 percent in accordance with ASHRAE 74. Thickness: 0.017 inches. Weight: 10.50 oz./sq. yd.

SW2900: Openness Factor: 5 percent in accordance with ASHRAE 74. Thickness: 0.017 inches. Weight: 11.90 oz./sq. yd.

SheerWeave Series SW2701/2703/2705 by Phifer. For interior use only. Duplex twill fabric, light outer panel color combined with dark interior color for thermal comfort and view-through. Flame retardant per NFPA 701 and BS 5867-2. California U.S. Title 19 compliant. Bacteria and Fungi Resistant per ASTM E2180. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Colors available: Oyster, Oyster/Beige, Oyster/Pewter, Oyster/Chestnut. Oyster/Pearl Grey and Oyster/Charcoal.

SW2701: Openness Factor: 1 percent in accordance with ASHRAE 74. Thickness: 0.026 inches. Weight: 14.10 oz./sq. yd.

SW2703: Openness Factor: 3 percent in accordance with ASHRAE 74. Thickness: 0.028 inches. Weight: 14 oz./sq. yd.

SW2705: Openness Factor: 5 percent in accordance with ASHRAE 74. Thickness: 0.025 inches. Weight: 11.80 oz./sq. yd.

SW2710: Openness Factor: 10 percent in accordance with ASHRAE 74. Thickness: 0.025 inches. Weight: 10.40 oz./sq. yd.

DRAPER[®]

Please note: See page 3 for more information regarding various fabric certifications

411 S. Pearl St., Spiceland, IN 47385 USA ■ 765-987-7999

www.draperinc.com ■ fax 765-987-7142

Copyright ©2011 Draper Inc. Form ShadeFabric_ReferenceSheet11-R2 Printed in U.S.A.

PROJECT: _____

ARCHITECT: _____

CONTRACTOR: _____

SUPPLIER: _____

DATE: _____ REVISED: _____

Specifications—Fabrics (continued)

SheerWeave Series SW3000 by Phifer. For interior use only. Approximately 65 percent vinyl coated fiberglass and 35 percent vinyl coated polyester woven into a vertically oriented mesh with Microban Protection. Flame retardant per NFPA 701. Bacteria and Fungi Resistant per ASTM D3273, ASTM D6329, ASTM E2180 and ASTM G21. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Lead free certified per RoHS. Chemical compliant per REACH (EC 1907/2006). Openness Factor: 14 percent in accordance with ASHRAE 74. Thickness: 0.028 inches. Weight: 13.46 oz./sq. yd. Colors available: Mushroom Sand, Pearl White, Custard Cream, Sand Dolair, Honey Sage, Pale Grey, Ninja Grey, Espresso and Chocolate.

SheerWeave SW5000 by Phifer. For interior use only. Polyester and vinyl coated polyester woven into a 42 x 20 mesh with Microban Protection. Fire Rating: Varies by color. Bacteria and Fungi Resistant per ASTM E2180 and ASTM G21. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Lead free certified per RoHS. Chemical compliant per REACH (EC 1907/2006). Openness Factor: Varies from 5%-10% by color in accordance with ASHRAE 74. Thickness: 0.038 inches. Weight: 14.50 oz./sq. yd. Colors available: Marble/Slate, Marble/Sand, Marble/Quartz, Wicker/Mushroom, Bark/Tiger Oak, Bark/Cedar, Rattan/Umber, Moire/Mocha, Bamboo/Birch, Honeycomb/Brown Sugar, Tweed/Oatmeal, Tweed/Buckeye, Thatch/Wheatgrass, Crepe/Toasted Coconut, Crepe/Jade, Crepe/Chestnut, Crepe/Granola, Crepe/Walnut, Crepe/Blackened Bronze, Seaglass/Gold, Seaglass/Chardoney, Seaglass/Crystal, Seaglass/Verde, Seaglass/Silver, Seaglass/Copper, Linen/Cream, Linen/Topaz, Linen/Fig, Linen/Cranberry, Linen/Cinnamon, Linen/Burlap, Digital Lines/Shimmer, Digital Lines/Caramel, Digital Lines/Raven, Digital Lines/Crystal, Digital Lines/Polished Silver, Digital Lines/Pearly Black, Filigree/Light Copper, Filigree/Toffee, Filigree/Polished Silver, Filigree/Crystal and Filigree/Frost.

SunTex 90 by Phifer. For exterior use only. Vinyl-coated polyester. 10 percent open in accordance with ASHRAE 74. Fire Rating NFPA 101-04 (Class A Rating), California Technical Bulletin 117 and UBC (Class 1). Bacteria and Fungi Resistant per ASTM E 2180 and G 22; includes Microban antimicrobial additives (see note below). GREENGUARD Indoor Air Quality Certified. Lead Free: RoHS / Directive 2002/95/EC, US Consumer Product Safety Commission Section 101, ANSI/WCMA A100.1-2007 for lead content and REACH (EC 1907/2006) compliant. GREENGUARD Children & Schools Certified. Oeko-Tex Certified. Thickness: 0.039 inches. Weight: 17.20 oz./sq. yd. Colors available: Beige, Black, Brown, Grey and Stucco.

SunTex 90 Design by Phifer. For exterior use only. Vinyl-coated polyester. 10 percent open in accordance with ASHRAE 74. Fire Rating NFPA 101 (Class A Rating), California Technical Bulletin 117 and UBC (Class 1). Bacteria and Fungi Resistant per ASTM E 2180 and G 22; includes Microban antimicrobial additives (see note below). GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools (SM) Certified. Oeko-Tex Certified. Thickness: 0.039 inches. Weight: 10.20 oz./sq. yd. Colors Available: Colors available: Coconut, Coral, Rattan, Toast, Toffee, Walnut and Wheat.

SheerWeave Series SW7000, as manufactured by Phifer. For interior use. 100% Polyester with Acrylic Foam Backing (PVC-Free). Fire Rating: California U.S. Title 19 (small scale), NFPA 701 TM#1 (small scale), BS 5867 2008 Part 2 Type B Performance. Bacteria and Fungal Resistance: ASTM G21-96, AATCC 174-1998 Part II and III. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Lead Free: RoHS / Directive 2002/95/EC. Openness Factor: 0 percent in accordance with ASHRAE 74. Thickness: .026 inches. Weight: 12.00 oz./sq. yd. Colors available: White, Birch, Sand, Wheat, Graphite, Onyx, Canyon and Mushroom.

SheerWeave® Series SW7100 by Phifer. For interior use. PVC-coated Fiberglass laminated with a 2-ply PVC film. Fire Rating: California U.S. Title 19 (small scale); NFPA 701 TM#1 (small scale) and BS 5867 2008 Part 2 Type B Performance. Bacteria and Fungal Resistance: ASTM E 2180, ASTM G21 and ASTM G22; Style 2000 face fabric includes Microban antimicrobial additives (see note below). Lead Free: RoHS / Directive 2002/95/EC and REACH (EC 1907/2006) compliant. Openness Factor: 0 percent in accordance with ASHRAE 74. Thickness: .023 inches. Weight: 19.80 oz./sq. yd. Colors available: White, White/Bone, White/Platinum, Bone, Bone/Platinum and Charcoal.

SheerWeave Series SW7500 by Phifer. For interior use. PVC-free coated polyester. Fire Rating: California U.S. Title 19 (small scale) and NFPA 701 TM#1 (small scale). Bacteria and Fungal Resistance: ASTM E 2180 and ASTM G 22. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Lead Free: RoHS / Directive 2002/95/EC. Openness Factor: 0 percent in accordance with ASHRAE 74. Thickness: 0.013 inches. Weight: 11.80 oz./sq. yd. Colors available: Ice, Coconut, Loft, Spirit, Dune, Starfish, Stone, Odyssey, Orient and Midnight.

Mermet

E-Screen by Mermet. For interior use. 36 percent PVC-coated fiberglass and 64 percent vinyl blend woven into high quality 2 x 2 basketweave. Flame retardant per NFPA 701. California U.S. Title 19 compliant. Bacteria and Fungi Resistant per ASTM G21. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Oeko-Tex Certified. Colors available: White, White/Linen, Linen, White/Perle, Charcoal/Grey, Charcoal, Charcoal/Bronze, Grey/White and Grey/Grey.

- 1%: Openness Factor: 1 percent in accordance with ASHRAE 74. Thickness: 0.020 inches. Weight: 13.30 oz./sq. yd.
- 3%: Openness Factor: 3 percent in accordance with ASHRAE 74. Thickness: 0.020 inches. Weight: 12.30 oz./sq. yd.
- 5%: Openness Factor: 5 percent in accordance with ASHRAE 74. Thickness: 0.020 inches. Weight: 12.10 oz./sq. yd.
- 10%: Openness Factor: 10 percent in accordance with ASHRAE 74. Thickness: 0.022 inches. Weight: 10.30 oz./sq. yd.

Flocke by Mermet. For interior use. 42 percent fiberglass, 51 percent acrylic and 7 percent cotton flocked backing. Mercury, bromine, lead and PVC-free. Fire Rating: NFPA 701. Openness Factor: 0 percent in accordance with ASHRAE 74. Thickness: .022 inches. Weight: 14.70oz./sq. yd. Colors available: Blanc, Chartreux, Loutre, Mississippi and Sahel.

M Screen by Mermet. For interior use. 36 percent PVC-coated fiberglass and 64 percent vinyl blend woven into high quality 1 by 2 weave textile appearance. Flame retardant per NFPA 701. California U.S. Title 19 compliant. Bacteria and Fungi Resistant per ASTM G21. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Oeko-Tex Certified. Colors available: White/White, White/Linen, Linen, White/Stone, White/Perle, Perle, Perle/Linen, Charcoal, Charcoal/Hunter, Linen/Ultra, Linen/Stone, Charcoal/Grey, White/Sable, Perle/Sable, Charcoal/Sable, Charcoal/Apricot, Charcoal/Ultra, Cocoa/Charcoal, Cocoa/Phoenix-Cocoa, White/Sable-Mustard, Linen/Sable-Cocoa, Sable/Straw-Cocoa, Charcoal/Brick Facade-Fall, Charcoal/Cocoa, Charcoal/Straw-Cocoa, White/Straw-Linen, Sable/Charcoal, Sable/Cocoa-Hazelnut, Charcoal/Phoenix-Cocoa, Cocoa/Brick Facade-Fall, Cocoa/Fall-Mustard, White/Sable-Cocoa, Cocoa/Sable-Straw, Sable/Mustard-Hazelnut, Cocoa/Phoenix-Hazelnut and Cocoa/Sable-Cocoa.

- 3%: Openness Factor: 3 percent in accordance with ASHRAE 74. Thickness: 0.022 inches. Weight: 12.70 oz./sq. yd.
- 5%: Openness Factor: 5 percent in accordance with ASHRAE 74. Thickness: 0.022 inches. Weight: 12.10 oz./sq. yd.

Natte by Mermet. For exterior use only. 42% Fiberglass / 58% Vinyl. 12 percent open in accordance with ASHRAE 74. Fire Rating: NFPA 701 TM#1, California U.S. Title 19. Bacteria and Fungi Resistant per ASTM G21. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Oeko-Tex Certified. Thickness: 0.021 inches. Weight: 13.9 oz./sq. yd. Colors available: Bronze, Charcoal, White/Stone, White/Mustard, Bronze/Grey, Bronze/Pearl, Bronze/Mustard, Charcoal Bronze, Charcoal/Fern, Bronze/Cocoa/Mandarin and White/Pearl-Grey.

S Screen by Mermet. For interior use. 33.6% Fiberglass / 59.6% PVC 6.8% Uncoated Polyester. Fire Rating: NFPA 701 TM#1, California U.S. Title 19. Bacteria and Fungi Resistant per ASTM G21. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Oeko-Tex Certified. Openness Factor: 4 percent in accordance with ASHRAE 74. Thickness: 0.037 inches. Weight: 18.90 oz./sq. yd. Colors available: Patina, Cork, Porcelain, Jute, Papyrus, Sepia, Marble, Granite, Carbon, Ginger, Clove, Nougat, Seasalt, Coffee Bean, Almond, Peppercorn, Licorice and Sesame.

Satine by Mermet. For exterior use. 42% Fiberglass / 58% Vinyl. 1 percent open in accordance with ASHRAE 74. Fire Rating: NFPA 701 TM#1, California U.S. Title 19. Bacteria and Fungi Resistant per ASTM G21. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Oeko-Tex Certified. Thickness: 0.030 inches. Weight: 15.8 oz./sq. yd. Colors available: White, White/Sable, White/Straw, Bronze, Bronze/Sable, Charcoal/Grey, Charcoal/Bronze and Charcoal.

SilverScreen by Mermet. For interior use only. Environmentally friendly formaldehyde free product, made of PVC-coated fiberglass, with silver backing on outside for glare control. Flame retardant per NFPA 701, NF P92-503, ISO 6941 and BS 5867-2. Oeko-Tex Certified. Openness Factor: 5 percent in accordance with ASHRAE 74. Thickness: 0.022 inches. Weight: 12.86 oz./sq. yd. Colors available: White, Beige, Light Grey, Black, Dark Grey, Dark Beige, Bronze, Chocolate/Brown, Misty Grey and Steel Grey.

T-Screen by Mermet. For interior use only. 36 percent fiberglass and 64 percent vinyl. Dark on one side, light on the other. Flame retardant per NFPA 701. California U.S. Title 19 compliant. Bacteria and Fungi Resistant per ASTM

Specifications—Fabrics (continued)

G21. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Oeko-Tex Certified. Openness Factor: 3 percent in accordance with ASHRAE 74. Thickness: 0.025 inches. Weight: 11.60 oz./sq. yd. Colors available: White/White, White/Pearl, White/Sable, White/Linen, White/Sable-Cocoa, White/Charcoal-Grey, White/Sable-Straw, White/Sable-Mustard, Cocoa/Cocoa, Cocoa/Sable/Linen, Cocoa/Phoenix-Mustard, Cocoa/Apricot-Mustard, Cocoa/Phoenix-Fall, Cocoa/Grey-Straw, Cocoa/Sable-Cocoa, Sable/Linen, Sable/Charcoal, Sable/Straw-Cocoa, Sable/Cocoa-Hazelnut, Charcoal/Grey, Charcoal/Charcoal, Charcoal/Linen-Pearl, Charcoal/Fall-Hazelnut and Charcoal/Sable-Cocoa.

Vela by Mermet. For interior use only. 100 percent polyester. Halogen, mercury, lead, and PVC-free. Flame retardant per NFPA 701, NF P92-512, and DIN 4102-1. California U.S. Title 19 compliant. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Oeko-Tex Certified. Openness Factor: 3 percent in accordance with ASHRAE 74. Thickness: 0.015 inches. Weight: 4.71 oz./sq. yd. Colors available: White, Pearl, Charcoal Bronze, Pearl Linen, Linen, Pewter and Charcoal.

Vienne by Mermet. For exterior use. 42% Fiberglass / 58% Vinyl. 10 percent open in accordance with ASHRAE 74. Fire Rating: NFPA 701 TM#1, California U.S. Title 19. Bacteria and Fungi Resistant per ASTM G21. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Oeko-Tex Certified. Thickness: 0.021 inches. Weight: 10.40 oz./sq. yd. Colors available: White, White/Linen, Bronze/Mandarin, Bronze/Straw, Bronze/Apricot, Charcoal/Grey, Charcoal/Pearl, Charcoal/Sable, Charcoal, Charcoal/Denim and Charcoal/Pine.

Vizela by Mermet. For interior use only. 100% Fiberglass, EVA Coating / PVC Free, lead free. Fire Rating: NFPA 701 TM#1, California U.S. Title 19, and NFP 92 503. GREENGUARD Indoor Air Quality Certified. Children & Schools Certified. Oeko-Tex Certified. Openness Factor: 1 percent in accordance with ASHRAE 74. Thickness: 0.013 inches. Weight: 8.7 oz./sq. yd. Colors available: Mississippi, Loutre, Chartreux, Sahel and Blanc.

Draper Exclusives:

GreenScreen Revive by Draper. For interior use. Environmentally certified, constructed of 100% polyester yarn. PVC-free fabric, with a minimum of 89% Repreve® recycled polyester. 100% recyclable. Made in the USA. Flame retardant per NFPA 701. California U.S. Title 19 compliant. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Lead free certified per RoHS. Colors available: White, Sand, Linen, Dusk, Wheat, Stone, Mushroom and Suede.

- 1%:** Openness Factor: 1 percent in accordance with ASHRAE 74. Thickness: .019 inches. Weight: 5.87 oz./sq. yd.
- 5%:** Openness Factor: 5 percent in accordance with ASHRAE 74. Thickness: .017 inches. Weight: 5.01 oz./sq. yd.

SunBloc Series SB9000 by Draper, Inc. For interior use only. Opaque, close woven fiberglass base textile with sun-resistant vinyl film bonded to each side. Same color both sides. Fire Rating: NFPA 701. Factor: 0 percent in accordance with ASHRAE 74. Thickness: 0.015 inches. Weight: 12 oz./sq. yd. Colors available: White, Ivory, Tan, Grey, Black, Champagne, Dark Grey and Oyster.

SunBloc Series SB9100 by Draper, Inc. For interior use only. Opaque, close woven fiberglass base textile with sun-resistant vinyl film bonded to each side. White color on exterior side. Maximum Width: 72 inches. Fire Rating: NFPA 701. Bacteria and Fungi Resistant per ASTM G21. Openness Factor: 0 percent in accordance with ASHRAE 74. Thickness: 0.013 inches. Weight: 12 oz./sq. yd. Colors available: Ivory/White, Grey/White, Chocolate/White, Wheat/White, Putty/White, Forest Green/White, Black/White, Burgundy/White, Navy/White, Dark Grey/White and Putty/Putty.

Ferrari

Soltis 99 by Ferrari. For interior use only. PVC-coated polyester with silver backing on outside and pre-tensioning process for dimensional stability. Flame retardant per NFPA 701. GREENGUARD Indoor Air Quality Certified. GREENGUARD Children & Schools Certified. Oeko-Tex Certified. Texyloop Certified. Openness Factor: 3 percent in accordance with ASHRAE 74. Thickness: 0.013 inches. Weight: 9 oz./sq. yd. Colors available: Ivory, White, Tan, Yellow, Light Grey, Silver, Black, Lemon Yellow, Peach, Platinum, Brown, Bisque, Moss, Dark Blue, Blue, Dark Grey and Sky Blue.

Rockland

Roc-Rol by Rockland Industries, Inc. For interior use only. Opaque, 70 percent PVC-free polyester and 30 percent cotton blend. White color on exterior side. Fire Rating: NFPA 701. Openness Factor: 0 percent in accordance with ASHRAE 74. Thickness: 0.025 inches. Weight: 13.50 oz./sq. yd. U.S. Patent 5,741,582, Rockland Industries, Inc. Colors available: White, Ivory, Pearl, Beige, Ecru, Slate, Sage, Jade, Plum, Silver Grey, Black and Hazelnut.

SheerWeave® is a registered trademark of Phifer.

Soltis® is a registered trademark of Ferrari.

Roc-rol™ is a trademark of Rockland Industries, Inc.

Specifications subject to change without notice.



From www.greenguard.org: "This standard is designed to define low-emitting materials suitable for environments where people, particularly children and sensitive adults, spend extended periods of time. These environments may include schools, daycares, healthcare facilities, homes and commercial spaces.

The GREENGUARD Children & Schools Certification Program's requirements comply with the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions from building products used in schools and other environments. As such, GREENGUARD Children & Schools Certified products can be used to earn valuable credits in the CHPS Best Practices Manual for K-12 schools, the US Green Building Council's LEED® Green Building Rating Systems, the Green Guide for Healthcare, the NAHB Green Building Guidelines, Green Globes, Regreen and many other building codes, standards and specifications.



Microban® antimicrobial protection inhibits the growth of damaging bacteria, mold and mildew on the fabric.



Texyloop is a closed loop system for the recycling of Polyester-PVC composite textiles. It is an initiative of the Ferrari® Group.



Oeko-Tex Standard 100 is an international testing and certification system for textiles. The standard limits the use of certain chemicals, including formaldehyde, pesticides, extractable heavy metals, chlorinated organic carriers and more.