

LIFTS AND MOUNTS LCD Lift A and B

CEILING MOUNTED/INSTALLED, LOWERED WHEN IN USE



Product: LCD Lift A., Eisenhower High School, Blue Island, IL, Photography: Rich Sistos, Itasca, IL

- The LCD Lift positions the projector just below the ceiling line and features two models to accommodate different projector sizes. Model A is designed to accommodate smaller projector sizes. Model B is designed to accommodate larger projector sizes.

Environmental airspace housing isolates and secures your lift and projector from the space above ceilings.

FEATURES

- Positions projector directly below the ceiling.
- Includes Environmental Airspace Housing to isolate projector from environmental airspace above ceiling.
- Includes ceiling closure panel available with flat closure or bomb bay style doors.
- Installation of factory installed cables for video and projector control available.
- Wall switch standard.
- WARRANTY: One year against defects in materials and workmanship.

OPTIONS

- Optional universal-style bracket for easy attachment of a variety of projector models.
- Optional IR or RF remote control, or integrate into your control system.

SIZES

- **LCD Lift A Maximum lifting capacity**
up to 65 lb (29 kg).
LCD Lift A dimensions bomb bay ceiling closure (WxD)
24-½" x 24-½" (62 cm x 62 cm)
Maximum projector size (HxWxD)
11" x 18" x 18" (28 cm x 46 cm x 46 cm)
- **Model B Maximum lifting capacity**
up to 65 lb (29 kg).
LCD Lift B dimensions bomb bay ceiling closure (WxD)
29-½" x 29-½" (75 cm x 75 cm)
Maximum projector size (HxWxD)
16" x 23" x 23" (41 cm x 58 cm x 58 cm)

SUPPORTING DOCUMENTS

All instructions, technical drawings and other supporting documents are located at: draperinc.com/Documents.aspx

For more information on this product visit: draperinc.com/liftsmounts/projectorlifts.aspx