


ELECTRIC Rolleramic

FREE-HANGING, CEILING- OR WALL-MOUNTED



- Engineered with a direct drive motor, the wall- or ceiling-mounted Rolleramic electric projection screen is an economical option for large venues in auditoriums, lecture halls, hospitals, hotels, and churches. The motor is housed in an all wood case and is insulated to minimize friction, which provides smooth, quiet operation.

THIS SCREEN IS FREE-HANGING
Free-hanging, fiberglass-backed projection screen maintains flatness thanks to the weight of the screen and bottom dowel.

FEATURES

- Available in NTSC, HDTV, AV and 16:10 format.
- Housed in ¾" (19 mm) warp resistant composition wood with hinged panel for motor compartment. Case finished with a coat of black primer paint.
- Heavy-duty electric projection screen with end mounted motor and direct drive.



OPTIONS

- Viewing Surfaces:** OptiView™ family.

WARRANTY

draperinc.com/warranty.aspx

SIZES

- Case dimensions** 9 1/8" high x 9 1/8" deep (23 cm x 23 cm).
- Maximum image width** up to 20' (610 cm) wide, depending on surface selection.
- 16:10 FORMAT: from 94" to 278" (239 cm to 706 cm) dia.
- 16:9 FORMAT: from 92" to 270" (234 cm to 686 cm) dia.
- 4:3 NTSC/PAL Format: from 72" to 300" (183 cm to 762 cm) dia.
- AV Format: from 50" x 50" to 240" x 240" (127 cm x 127 cm to 610 cm x 610 cm) viewing area.
- Custom sizes available.

SUPPORTING DOCUMENTS

All instructions, technical drawings and other supporting documents are located at: draperinc.com/documents.aspx

For more information on this product visit:

draperinc.com/projectionscreens/electricscreens.aspx