

# FIXED SCREEN VERSAROLL™

DESIGNED TO BE WALL-MOUNTED AND/OR FLOWN, CURVED AND SEMI-RIGID REAR PROJECTION SCREEN



THIS SPECIAL SUBSTRATE, TYPICALLY  $\frac{3}{16}$ " (.48CM) THICK, HELPS ADDRESS THE ADDED COSTS OF SHIPPING AND HANDLING OF A VERY LARGE SCREEN.

■ VersaRoll utilizes the same rear projection screen coatings as the IRUS and Cinescreen® applying them to a unique substrate. The semi-rigid material ships rolled up inside a crate to provide ease of mobility and maneuverability in gaining access inside buildings for very large projection screens. This product addresses the added costs of shipping and handling associated with very large screens, while providing ease of installation. It also ships with a specially-designed frame for a flat screen install or to help flatten the screen for blending. VersaRoll is an excellent product for curved screen applications using conventional rear coatings or a custom front screen coating.

## FEATURES

- Curved VersaRoll and Semi-Rigid screens are available by special quotation only.
- Available as a front or rear projection screen.
- VersaRoll curved screens typically utilize  $\frac{3}{16}$ " (5 mm),  $\frac{1}{4}$ " (6 mm), or  $\frac{1}{8}$ " (3 mm) thick, Cinescreen® or IRUS substrate.
- Semi-Rigid screens typically utilize a  $\frac{3}{16}$ " (5 mm) thick acrylic substrate.
- Choose coating options from CineScreen® or IRUS substrates.

## OPTIONS

- **These products are custom quoted.**
- Cinescreen or IRUS coatings.

## SUPPORTING DOCUMENTS

All instructions, technical drawings and other supporting documents are located at: [draperinc.com/documents.aspx](http://draperinc.com/documents.aspx)

Draper is uniquely positioned to excel at custom solutions for rear projection needs by tapping into our experienced product and engineering design team.

## SIZES

- **Maximum standard size for  $\frac{1}{4}$ "** (6 mm) thick curved screens is 104" (264 cm) high x 192" (488 cm) wide. Larger sizes are available by custom quote.
- **Maximum standard size for  $\frac{1}{8}$ "** (3 mm) thick curved screens is 100" (254 cm) high x 360" (914 cm) wide. Larger sizes available by custom quote.
- **Maximum standard size for  $\frac{3}{16}$ "** (5 mm) thick curved screens is 100" (254 cm) high x 360" (914 cm) wide. Larger sizes are available by custom quote.
- **Maximum size for a VersaRoll™ Semi-Rigid screen** is 100" (254 cm) high.
- **Minimum curve radius is 8'** (244 cm). Some tighter radius curves may require custom framing. Call for details. Custom sizes available.

For more information on this product visit: [draperinc.com/projectionscreens/fixedscreens.aspx](http://draperinc.com/projectionscreens/fixedscreens.aspx)