

MANUAL CLUTCH FLEXSHADE® NEXD

NEW! FULLY ASSEMBLED CASSETTE STYLE



LEFT: FlexShade® NEXD Cassette Style.
ABOVE: Idler Endcap (left)
and Clutch Assembly

■ NEXD is available in three sizes, slim, small and large. Where slim and small are available in same sizes, small will be the default choice. You can override to the slim size where appropriate or large when necessary. The Clutch-Operated FlexShade® NEXD provides for an easy install with a variety of hardware options. Designed for wall, ceiling and jamb installation. No separate brackets are required for mounting. This premium manually-operated window shade comes standard with a height-adjustable idler endcap for fine leveling adjustments after installation. The Clutch-Operated FlexShade® NEXD features a heavy-duty field convertible clutch built for durability that provides ease-of-use and low maintenance for commercial, healthcare, institutional, or educational settings.

FEATURES

- Maximum shade width for 3-³/₁₆" (81 mm) clutch is 84" (213 cm), depending on fabric selection. Optional dual rollers available upon request.
- Bead chain clutch operator mounted right (standard) or left-hand operation.
- Clutch available in white (standard) or black.
- Stainless steel bead chain (standard).
- Steel mounting bracket with integrated NEXD Clutch.
- Height-adjustable idler bracket for fine leveling adjustments after installation.
- Comes with mounting endcaps (standard) with a 3-³/₁₆" (81 mm) profile. Optional fascia with endcaps or cassette-style system available for slim sizes. Fully assembled cassette-style system has a 3-³/₈" (86 mm) profile.
- Pre-drilled jamb mounting holes.
- Product designed for interior use.

OPTIONS

- Polyester chain available in white, black, brown, grey, or ivory at no extra charge.
- Optional fascia with endcaps or cassette-style system available.
- Hardware finish choices: clear anodized (standard), black, white, ivory, or charcoal bronze. Custom powder coat colors available.
- Adhesive attachment available upon request in place of spline attachment (standard).
- Clutch-operated products can be ANSI/WCMA A100.1 compliant for areas where small children are present. Details here.

SIZES

- Maximum shade width for 3 ³/₁₆" (81 mm) clutch is 84" (213 cm), depending on fabric selection.

FABRIC OPTIONS.

windowshades/fabricoptions.aspx

WARRANTY

warranty.aspx

SUPPORTING DOCUMENTS

All instructions, technical drawings and other supporting documents are located at: documents.aspx

For more information on this product visit: windowshades/manualshades.aspx