

Overview

The AV Gateway is used to integrate with 3rd party control systems such as Lutron, Crestron and others.

Features

- Supports RS-232 and RS-485
- 6 Contact closure inputs
- Low voltage trigger
- IR receiver input
- LCD display allows for commissioning of serial groups

Compatible Components

Tools	Motor Limit Tool	PN: C202.030
User Input Devices	Single Zone Wall Switch*	PN: C112.161
	Dual Zone Wall Switch*	PN: C112.162
	Handheld Remote	PN: C156.270
Network Devices	Network Device Connector	PN: C156.267
	Wireless Network Gateway	PN: C156.268
	AV Gateway*	PN: C156.269
	Contact Closure Interface*	PN: C156.273
	Sensor/Schedule Interface*	PN: C156.272

*One NDC is included with each of these devices



TECHNICAL SPECIFICATIONS

Material: ABS plastic

Dimensions: 4 7/8" x 3 1/4" x 1 1/4" 124 x 83 x 32mm

Operating Temp: Ambient

Shipping Weight: 1 lb 0.45 kg

Indoor use only

Part of the IntelliFlex I/O System

IntelliFlex I/O by Draper is a complete control solution for motorized roller shades. Intelligent motors are connected to wall switches and other input devices through a wired network. This network allows communication between the devices and also distributes power to them from the motors, eliminating the need for external power supplies. Configuration is done from the devices themselves, with no need for a computer connection to the network. Networks can include up to 120 devices and extend to 4000 feet in total with no further restrictions on connections between components.

IntelliFlex I/O System Overview - AV Gateway

