

# Cordless FlexShade®

Cordless, manual roller shade with decorative headrail

## SUBMITTAL TECHNICAL INFO

Please check all appropriate selections and attach room schedule with verified dimensions.

### CORDLESS FLEX

Fabric Series: \_\_\_\_\_

Color Name / Number: \_\_\_\_\_

Openness Factor: \_\_\_\_\_


Please see [Fabric Options](#) on the [Draper® website](#) for fabric colors and specifications.

### Select Fabric Orientation

- Regular Roll (from back of roller) (standard)
- Reverse Roll (from front of roller)

### Select Mounting Style

- Inside Mount
- Outside Mount



INSIDE MOUNT



OUTSIDE MOUNT

### Select Hem Bar Style

- Closed Pocket - 1" (25mm) Elliptical Slat (standard)
- Open Pocket - 1" (25mm) Elliptical Slat
- Flat Rectangular Exposed Hem Bar
  - Small - 7/8" x 5/16" (22mm x 8mm)
  - Large - 1 1/2" x 5/16" (38mm x 8mm)
- Small Round Exposed Hem Bar - 3/4" (19mm) diameter

### Available Sizes:

WIDTH:	2'	3'	4'	5'	6'	7'	8'
HEIGHT							
2'							
3'							
4'							
5'							
6'							
7'							
8'							

Fabric weight and thickness will determine maximum shade size.

### Specifications

**MANUALLY-OPERATED WINDOW SHADES WITH INDEPENDENT CONTROL:** ANSI/WCMA A100.1 compliant, manually-operated, vertical roll-up, fabric window shade with components necessary for complete installation; Cordless FlexShade® roller-operated shade as manufactured by Draper, Inc.

**OPERATION:** Spring roller operating mechanism with metal roller containing heavy-duty spring with positive locking mechanism permitting shade to be stopped at each half turn of roller. Spring sized by manufacturer to accommodate shade size.

**MOUNTING BRACKETS:** Metal. Provide size compatible with roller size. Mounted to [ceiling] [wall] [jamb].

**ROLLER TUBE:** Fabricated from extruded aluminum. Roller outer diameter 1.5 inches (38 mm).

**FABRIC TO TUBE ATTACHMENT:** Connected to the roller tube with LSE (low surface energy) double sided adhesive specifically developed to attach coated textiles to metal. Adhesive attachment to eliminate horizontal impressions in fabric.

**ROLLER SPRING TENSION:** To be adjustable from the roller brackets to ensure correct tension for proper retraction.

### HEM BAR:

**CLOSED POCKET ELLIPTICAL SLAT:** 1" (25mm) aluminum elliptical slat inside of a 1 1/8" (41mm) pocket with heat sealed ends.

**OPEN POCKET ELLIPTICAL SLAT:** 1" (25mm) aluminum elliptical slat with plastic ends inside of a 1 1/8" (41mm) pocket.

**FLAT EXPOSED HEM BAR: SMALL:** 7/8" x 5/16" (22mm x 8mm) and **LARGE:** 1 1/2" x 5/16" (38mm x 8mm) aluminum rectangular hem bar with plastic endcaps. Powder coated in black, bronze, ivory, white, or clear anodized.

**SMALL ROUND EXPOSED HEM BAR:** 3/4" (19mm). Aluminum with plastic end caps.

### DOWNLOADABLE 3-PART SPECIFICATIONS:

available at [www.draperinc.com](http://www.draperinc.com)

Please note: Dimensions of rollers, operators, and hardware at manufacturer's discretion.



Draper, Inc. | 411 S. Pearl St. Spiceland, IN 47385  
draperinc.com | 765.987.7999 | 800.238.7999

© 2021 All Rights Reserved | FORM: FlexShade\_Cordless\_Sub21

PROJECT: \_\_\_\_\_

ARCHITECT: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_

SUPPLIER: \_\_\_\_\_

DATE: \_\_\_\_\_ REVISED: \_\_\_\_\_

## Components

