

Style 7400
BLACKOUT

Style 7450
LIGHT-FILTERING



U80 Cotton

U81 Parchment

U82 Sesame

U83 Pebble

U84 Seagrass

U85 Shale

U86 Spice

U87 Flint



U80 Cotton

U81 Parchment

U82 Sesame

U83 Pebble

U84 Seagrass

U85 Shale

U86 Spice

U87 Flint

Sheerweave® Style SW7400 / 7450

A picture of refined elegance, Style 7400 layers a subtle textured pattern over a soft, luxurious blackout backing for total light blockage. Offering the face fabric of Style 7400, Style 7450 filters natural light while illuminating interior spaces. These fabrics are suitable for roller shade, Roman shade and panel track systems.

SHEERWEAVE STYLE SW7400 / 7450

STANDARD WIDTH	118" (300cm).	FABRIC THICKNESS	7400: 0.029 in (0.74 mm)	7450: 0.0118 in (0.30 mm)
ROLL LENGTH	30 Linear Yards (27.4 lm).	OPENNESS FACTOR	7400: Opaque	7450: Light-Filtering
COMPOSITION	7400: 100% Polyester with Acrylic Foamed Backing 7450: 100% Polyester with Acrylic Coating	ACOUSTICAL VALUE	7400: NRC 0.05 / SAA 0.03	7450: NRC 0.25 / SAA 0.25
MESH WEIGHT	7400: 12.53 oz/yd ² (425 g/m ²) 7450: 6.19 oz/yd ² (210 g/m ²)	ACOUSTICAL PERFORMANCE	NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with ASTM C423-09a.	

SPECIFICATIONS

FIRE CLASSIFICATION	Style 7400: NFPA 101 (Class A Rating), IBC Section 803.1.1 (Class A Rating), California U.S. Title 19 (small scale), NFPA 701 TM#1 (small scale), CAN/ULC-S 109 (large and small scale), CAN/CGSB 2-4.162-M80, NFPA 701 TM#2 (large scale). Style 7450: NFPA 101 (Class A Rating), IBC Section 803.1.1 (Class A Rating), California Technical Bulletin 117.
BACTERIA AND FUNGAL RESISTANCE	ASTM G21-96, AATCC 174-1998 Part II and III.
ENVIRONMENTAL CERTIFICATION	Certified to GREENGUARD and GREENGUARD Gold standards for low chemical emissions into indoor air during product usage.
LEAD FREE	RoHS/Directive 2002/95/EC, ANSI/WCMA A 100.1-2007 for lead content, US Consumer Product Safety Commission Section 101.
STANDARD USES	Roller shades & panel tracks.
UV PROTECTION	Style 7400 received the Seal of Approval by the Melanoma International Foundation (MIF) for effectiveness in preventing sun damage to the skin or eyes.
WARRANTY	5-year interior.
CLEANING INSTRUCTIONS	Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to insure compatibility. Railroading this fabric is not recommended. Colors may vary slightly from swatch samples. All variations are within industry standards.

TECHNICAL DATA

COLOR	NUMBER	SOLAR OPTICAL PROPERTIES				SHGC/G VALUE g-tot (glass & blind)	
		TS%	RS%	AS%	TV%	Single 1/4 CL	Insulating 1HA
Cotton	U80	0	64	36	0	0.27	0.21
Parchment	U81	0	64	36	0	0.27	0.21
Sesame	U82	0	64	36	0	0.27	0.21
Pebble	U83	0	64	36	0	0.27	0.21
Seagrass	U84	0	64	36	0	0.27	0.21
Shale	U85	0	64	36	0	0.27	0.21
Spice	U86	0	64	36	0	0.27	0.21
Flint	U87	0	64	36	0	0.27	0.21



PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL COM/IGG
UL 2818



MIF Seal of
Approval



411 S. Pearl St. | Spiceland, IN 47385
765.987.7999 | 800.238.7999
draperinc.com



© SheerWeave is a registered trademark of PHIFER INCORPORATED.
© MICROBAN is a registered trademark of Microban Products Company.
TM UL, the UL logos and the UL mark are trademarks of UL LLC.
© PHIFER INCORPORATED V18 3033833

*TS - Solar Transmittance, RS - Solar Reflectance, AS - Solar Absorptance, TV - Visual Transmittance *SHGC = Solar Heat Gain Coefficient *1/4 CL = 1/4" Clear Glass, 1 HA = 1" Heat Absorbing Glass *Fabrics Installed Internally, Zero-Degree Profile Angle *Solar Heat Gain Coefficient (SHGC) shown calculated according to Office of Building Technology, State and Community Programs, Energy Efficiency and Renewable Energy, U.S. Department of Energy's definition of SHGC. SHGC represents the percentage of solar heat gain that is transmitted to the interior through the glass and shading system. If you are using glass whose performance is listed in terms of SC, you may convert to SHGC by multiplying the SC by 0.87.