

STYLE PW4901 / 4903

**Style PW4901**  
(1% open)



P06 Chalk

**Style PW4903**  
(3% open)



P06 Chalk

**The above styles are also available in the colors shown below.**



Q27 Soft Grey



V10 Ebony



P26 Chalk / Wheat  
face & back



Q23 Whitesands  
face & back



Q25 Birch  
face & back



Q22 Flaxen  
face & back



Q26 Cobblestone  
face & back



V03 Pewter / Chalk  
face & back




Q07 Kettal Grey  
face & back





P25 Chalk / Black  
face & back



V28 Slate  
face & back



Q16 Tobacco  
face & back



# Sheerweave® Style PW4901 / 4903

Form follows function in this unique combination of color and weave. Using thin and light weight vinyl-coated polyester yarns, Styles 4901 and 4903 are as versatile as they are beautiful. Styles 4901 and 4903 can also be used in exterior shading systems.

## SHEERWEAVE STYLE PW4901 / 4903

STANDARD WIDTH	63" and 98" (160 cm and 248.9 cm)	FABRIC THICKNESS	<b>4901 1%:</b> 0.028 in (0.71 mm)	<b>4903 3%:</b> 0.027 in (0.69 mm)
ROLL LENGTH	30 Linear Yards (27.4 lm)	OPENNESS FACTOR	<b>4901 1%:</b> Approximately 1%	<b>4903 3%:</b> Approximately 3%
COMPOSITION	17% Polyester / 83% Vinyl on Polyester	UV BLOCKAGE	<b>4901 1%:</b> Approximately 99%	<b>4903 3%:</b> Approximately 97%
MESH WEIGHT	<b>4901 1%:</b> 15.85 oz/yd <sup>2</sup> (573 g/m <sup>2</sup> ) <b>4903 3%:</b> 14.9 oz/yd <sup>2</sup> (505.20 g/m <sup>2</sup> )	ACOUSTICAL VALUE	<b>4901 1%:</b> NRC 0.60 / SAA 0.59 <b>4903 3%:</b> NRC 0.25 / SAA 0.25	
		ACOUSTICAL PERFORMANCE	NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with ASTM C423-09a.	

## SPECIFICATIONS

FIRE CLASSIFICATION	California U.S. Title 19 (small scale), NFPA 701 TM#1 (small scale), NFPA 101 (Class A Rating), IBC Section 803.1.1 (Class A Rating), BS 5867 Part 2 Type B Performance, NFPA 701 TM#2 (large scale), CAN/ ULC-S 109 (large and small scale), CAN/CGSB2-4. 162-M80.
BACTERIA AND FUNGAL RESISTANCE	ASTM E 2180, ASTM G21, ASTM G22, AATCC30 Part 3, ASTM D 3273, GREENGUARD Mold and Bacteria Standard ASTM 6329; includes Microban antimicrobial additives.
ENVIRONMENTAL CERTIFICATION	Certified to GREENGUARD and GREENGUARD Gold standards for low chemical emissions into indoor air during product usage.
SAFE USE	RoHS/Directive 2002/95/EC, US Consumer Product Safety Commission Section 101, ANSI/WCMA A 100.1-2007 for lead content and REACH (EC 1907/2006) compliant.
STANDARD USES	Roller shades, Roman shades and panel tracks.
UV PROTECTION	Seal of Approval by the Melanoma International Foundation (MIF) for effectiveness in preventing sun damage to the skin or eyes.
WARRANTY	10-year interior, 5-year exterior.

## TECHNICAL DATA

		SOLAR OPTICAL PROPERTIES								SHGC/G VALUE g-tot (glass & blind)			
		TS%		RS%		AS%		TV%		Single 1/4 CL Insulating 1HA		Single 1/4 CL Insulating 1HA	
OPENNESS		1%	3%	1%	3%	1%	3%	1%	3%	1%		3%	
COLOR	NUMBER	Rm/St*	Rm/St*	Rm/St*	Rm/St*	Rm/St*	Rm/St*	Rm/St*	Rm/St*	Rm/St*	Rm/St*	Rm/St*	Rm/St*
Chalk	P06	9/9	11/11	83/83	81/81	8/8	8/8	7/7	10/10	0.18/0.18	0.17/0.17	0.19/0.19	0.17/0.17
Chalk / Black	P25	1/1	3/3	22/54	25/56	77/45	72/41	1/1	3/3	0.50/0.33	0.32/0.24	0.49/0.32	0.32/0.23
Chalk / Wheat	P26	6/6	9/9	65/75	65/73	29/19	26/18	6/6	9/9	0.28/0.22	0.22/0.19	0.28/0.23	0.22/0.19
Kettal / Grey	Q07	3/3	4/4	48/37	47/37	49/60	49/59	3/3	5/5	0.37/0.43	0.26/0.29	0.37/0.43	0.26/0.29
Tobacco	Q16	2/2	3/3	8/6	8/6	90/92	89/91	2/2	4/4	0.58/0.59	0.36/0.37	0.58/0.59	0.37/0.37
Flaxen	Q22	3/3	6/6	42/57	43/57	55/40	51/37	3/3	7/7	0.40/0.31	0.27/0.23	0.40/0.32	0.27/0.23
Whitesands	Q23	7/7	9/9	65/67	63/67	28/26	28/24	6/6	8/8	0.28/0.27	0.22/0.21	0.30/0.27	0.23/0.21
Birch	Q25	5/5	7/7	57/64	56/63	38/31	37/30	4/4	7/7	0.32/0.28	0.23/0.22	0.25/0.29	0.24/0.22
Cobblestone	Q26	3/3	4/4	36/55	38/56	61/42	58/40	4/4	4/4	0.43/0.33	0.29/0.24	0.43/0.32	0.29/0.23
Soft Grey	Q27	5/5	8/8	58/58	57/57	37/37	35/35	4/4	8/8	0.31/0.31	0.23/0.23	0.32/0.32	0.23/0.23
Pewter / Chalk	V03	3/3	4/4	56/30	53/29	41/67	43/67	4/4	5/5	0.32/0.46	0.23/0.30	0.34/0.47	0.24/0.30
Ebony	V10	1/1	3/3	5/5	5/5	94/94	92/92	1/1	5/5	0.59/0.59	0.36/0.36	0.60/0.60	0.37/0.37
Slate	V28	2/2	3/3	11/8	12/8	87/90	85/89	3/3	4/4	0.57/0.58	0.36/0.36	0.55/0.58	0.35/0.37

\*Rm/St = Room side / Street side



**PW4901** ●●●●●●●●○ **PW4903** ●●●●●●●●○

\*TS - Solar Transmittance, RS - Solar Reflectance, AS - Solar Absorptance, TV - Visual Transmittance \*SHGC = Solar Heat Gain Coefficient \*1/4 CL = 1/4" Clear Glass, 1 HA = 1" Heat Absorbing Glass \*Fabrics Installed Internally, Zero-Degree Profile Angle \*Solar Heat Gain Coefficient (SHGC) shown calculated according to Office of Building Technology, State and Community Programs, Energy Efficiency and Renewable Energy, U.S. Department of Energy's definition of SHGC. SHGC represents the percentage of solar heat gain that is transmitted to the interior through the glass and shading system. If you are using glass whose performance is listed in terms of SC, you may convert to SHGC by multiplying the SC by 0.87.



411 S. Pearl St. | Spiceland, IN 47385  
765.987.7999 | 800.238.7999  
draperinc.com



© SheerWeave is a registered trademark of PHIFER INCORPORATED.  
© MICROBAN is a registered trademark of Microban Products Company.  
TM UL, the UL logos and the UL mark are trademarks of UL LLC.  
© PHIFER INCORPORATED V18 3034980