

STYLE SW7000 BLACKOUT FABRIC



SW7000-P63
Birch



SW7000-P62
White



SW7000-P64
Sand



SW7000-Q57
Wheat



SW7000-Q58
Mushroom




SW7000-U67
Canvas



SW7000-U69
Cocoa



SW7000-V41
Canyon



SW7000-V39
Graphite



SW7000-V40
Onyx

Sheerweave® Style SW7000 Blackout Fabric

Style 7000 is uniquely designed to provide total light blockage when complete room darkening is needed. With a broad range of decorator colors, the look and feel of rich cloth and a PVC-free composition, Style 7000 will enhance the beauty and function of both commercial and residential spaces. All style 7000 colors have an off-white backing.

SHEERWEAVE STYLE 7000 Blackout

| | | | |
|-------------|---|------------------------|---|
| WIDTHS | 94" and 118" (238.8cm and 300cm) | FABRIC THICKNESS | 0.030 in (0.76 mm) |
| ROLL LENGTH | 30 Linear Yards (27.4 lm) | OPENNESS FACTOR | Opaque |
| COMPOSITION | 100% Polyester with Acrylic Flocked Backing | ACOUSTICAL VALUE | NRC 0.10 / SAA 0.08 |
| MESH WEIGHT | 13.92 oz/yd ² (472.97 g/m ²) | ACOUSTICAL PERFORMANCE | NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with ASTM C423-09a. |

SPECIFICATIONS

| | |
|--------------------------------|--|
| FIRE CLASSIFICATION | California U.S. Title 19 (small scale), NFPA 701 TM#1 (small scale), BS 5867 Part 2 Type B Performance, CAN/ULC-S 109 (large and small scale), CAN/CGSB2-4.162-M80, IBC Section 803.1.1 (Class A Rating), NFPA 101 (Class A Rating). |
| BACTERIA AND FUNGAL RESISTANCE | ASTM G21, AATCC 174-1998 Part II and III. |
| ENVIRONMENTAL CERTIFICATION | Certified to GREENGUARD and GREENGUARD Gold standards for low chemical emissions into indoor air during product usage. |
| LEAD FREE | RoHS/Directive 2002/95/EC, US Consumer Product Safety Commission Section 101 and ANSI/WCMA A 100.1-2007 for lead content. |
| Standard Uses | Roller shades & panel tracks. |
| UV Protection | Seal of Approval by the Melanoma International Foundation (MIF) for effectiveness in preventing sun damage to the skin or eyes. |
| Warranty | 5-year interior |

STYLE 7000 BLACKOUT

| CODE / COLOR | SOLAR OPTICAL PROPERTIES | | SHGC/G VALUE g-tot (glass & blind) | |
|--------------|--------------------------|----|------------------------------------|------|
| | RS | AS | 1/4 CL | 1 HA |
| P62 White | 64 | 36 | 0.27 | 0.21 |
| P63 Birch | 64 | 36 | 0.27 | 0.21 |
| P64 Sand | 64 | 36 | 0.27 | 0.21 |
| Q57 Wheat | 64 | 36 | 0.27 | 0.21 |
| Q58 Mushroom | 64 | 36 | 0.27 | 0.21 |
| V39 Graphite | 64 | 36 | 0.27 | 0.21 |
| V40 Onyx | 64 | 36 | 0.27 | 0.21 |
| V41 Canyon | 64 | 36 | 0.27 | 0.21 |
| U67 Canvas | 64 | 36 | 0.27 | 0.21 |
| U69 Cocoa | 64 | 36 | 0.27 | 0.21 |



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL COM/GG
UL 2818



MIF Seal of Approval



PVC Free



Safe Use



Flame Retardant



Energy Saving



Printable



5 YEAR Interior Warranty



Phthalate Free



411 S. Pearl St. | Spiceland, IN 47385
765.987.7999 | 800.238.7999
draperinc.com

*TS - Solar Transmittance, RS - Solar Reflectance, AS - Solar Absorptance, TV - Visual Transmittance *SHGC = Solar Heat Gain Coefficient *1/4 CL = 1/4" Clear Glass, 1 HA = 1" Heat Absorbing Glass *Fabrics Installed Internally, Zero-Degree Profile Angle *Solar Heat Gain Coefficient (SHGC) shown calculated according to Office of Building Technology, State and Community Programs, Energy Efficiency and Renewable Energy, U.S. Department of Energy's definition of SHGC. SHGC represents the percentage of solar heat gain that is transmitted to the interior through the glass and shading system. If you are using glass whose performance is listed in terms of SC, you may convert to SHGC by multiplying the SC by 0.87.

PHIFER
INCORPORATED

© SheerWeave is a registered trademark of PHIFER INCORPORATED.
© MICROBAN is a registered trademark of Microban Products Company.
TM UL, the UL logos and the UL mark are trademarks of UL LLC.
© PHIFER INCORPORATED V18 3033833