



8000 S01 Snow



8000 S02 Eggshell



8000 S03 Ecrú



8000 S04 Silver



8000 S05 Smoke



8000 S06 Seal



8000 S07 Kohl

# SheerWeave® Style SW8000 Fabric

Cradle to Cradle Certified™ Bronze and constructed from 100% polyester yarn, Style 8000 is strong, lightweight, and 100% recyclable. The unique 2x2 basketweave provides excellent fabric stability and enhances outward views.

## BENEFITS OF STYLE 8000 INCLUDE:

- Cradle to Cradle Certified™ Bronze
- 100% Recyclable
- PVC free
- Halogen free
- Phthalate free
- Improved energy efficiency in dark colors
- LEED Material Ingredient Disclosure Credit Eligible

## SHEERWEAVE STYLE 8000

STANDARD WIDTH	118" (300cm)	FABRIC THICKNESS	0.019 in (0.47 mm)
ROLL LENGTH	30 Linear Yards (27.4 lm)	OPENNESS FACTOR	Approximately 3%
COMPOSITION	100% Polyester	ACOUSTICAL VALUE	NRC 0.20 / SAA 0.22
MESH WEIGHT	7.35 oz/yd <sup>2</sup> (249 g/m <sup>2</sup> )	ACOUSTICAL PERFORMANCE	NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with ASTM C423-09a

## SPECIFICATIONS

FIRE CLASSIFICATION	California U.S. Title 19 (small scale), NFPA 701 TM#1 (small scale), NFPA 101 (Class A Rating), IBC Section 803.1.1 (Class A Rating), BS 5867 Part 2 Type B Performance, NFPA 701 TM#2 (large scale), CAN/ULC-S 109 (large and small scale), B1 (DIN 4102-1), CAN/CGSB2-4.162-M80
BACTERIA AND FUNGAL RESISTANCE	ASTM E 2180 and ASTM G21
ENVIRONMENTAL CERTIFICATION	Cradle to Cradle Certified™ Bronze. Certified to GREENGUARD and GREENGUARD Gold standards for low chemical emissions into indoor air during product usage.
SAFE USE	RoHS/Directive 2002/95/EC, REACH (EC 1907/2006) compliant, US Consumer Product Safety Commission Section 101 and ANSI/WCMA A 100.1-2007 for lead content.
STANDARD USES	Roller shades & panel tracks.
UV PROTECTION	Seal of Approval by the Melanoma International Foundation (MIF) for effectiveness in preventing sun damage to the skin or eyes.
WARRANTY	5-year interior.

## STYLE 8000 3%

CODE	COLOR	SOLAR OPTICAL PROPERTIES				SHGC/G VALUE g-tot (glass & blind)	
		Ts%	Rs%	As%	Tv%	Single	Insulating
S01	Snow	38	54	8	36	0.40	0.27
S02	Eggshell	37	52	11	35	0.41	0.27
S03	Ecru	30	49	21	25	0.42	0.28
S04	Silver	30	46	24	22	0.44	0.29
S05	Smoke	23	38	39	9	0.46	0.30
S06	Seal	21	33	46	8	0.49	0.31
S07	Kohl	18	26	56	7	0.51	0.33



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS  
UL.COM/GG  
UL 2818



MIF Seal of Approval



411 S. Pearl St. | Spiceland, IN 47385  
765.987.7999 | 800.238.7999  
draperinc.com

**PHIFER**  
INCORPORATED

© SheerWeave is a registered trademark of PHIFER INCORPORATED.  
TM Cradle to Cradle Certified is a mark licensed by the Cradle to Cradle Products Innovation Institute.

TM UL, the UL logos and the UL mark are trademarks of UL LLC.

© PHIFER INCORPORATED V18 3035030

\*Ts - Solar Transmittance, Rs - Solar Reflectance, As - Solar Absorptance, Tv - Visual Transmittance \*SHGC = Solar Heat Gain Coefficient \*1/4 CL = 1/4" Clear Glass, 1 HA = 1" Heat Absorbing Glass \*Fabrics Installed Internally, Zero-Degree Profile Angle \*Solar Heat Gain Coefficient (SHGC) shown calculated according to Office of Building Technology, State and Community Programs, Energy Efficiency and Renewable Energy, U.S. Department of Energy's definition of SHGC. SHGC represents the percentage of solar heat gain that is transmitted to the interior through the glass and shading system. If you are using glass whose performance is listed in terms of SC, you may convert to SHGC by multiplying the SC by 0.87.